

BAHRAIN LUBRICANTS SEMI SYNTHETIC ENGINE OIL SAE 10W-40 API SN

(Premium Performance Semi-Synthetic Engine Oils)

DESCRIPTION

BAHRAIN LUBRICANTS SEMI SYNTHETIC ENGINE OIL SAE 10W-40 API SN is enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. They are designed to provide an excellent level of protection and performance under the most demanding conditions.

APPLICATIONS

BAHRAIN LUBRICANTS SEMI SYNTHETIC ENGINE OIL SAE 10W-40 API SN is formulated to give you confidence of protection beyond that of conventional oils. Particularly recommended for - Latest gasoline engine technologies, Passenger cars, SUV's, light trucks and vans, Stop and Go City Driving, Normal to severe operating conditions, Turbo-Chargers & High Performance Engines.

PROPERTIES

BAHRAIN LUBRICANTS SEMI SYNTHETIC ENGINE OIL SAE 10W-40 API SN is high performance industry proven products so you can trust you will get the performance you want from your vehicle. Low friction semi-synthetic formulation increases engine efficiency and offers greater fuel economy & also helps to promote long engine life.

PERFORMANCE FEATURES AND BENEFITS

- Superior engine protection during start up
- Superior engine wear protection
- Minimizes sludge formation
- Reduces wear by controlling soot deposits
- Extension of engine's lifetime
- Reduced high temperature engine deposits
- Reduces wear due to advanced base oils
- Can be used in both Diesel & LPG engines
- Provides improved fuel economy
- Suitable for hydraulically actuated injectors
- Safe for wet clutch motorcycles
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures

RECOMMENDATIONS / SPECIFICATIONS

International Standards : API SN, ACEA: A3/B4,C3, ILSAC GF-5, GF-4, JASO SG+

MEETS OR EXCEEDS : Opel GM-LL-A/B-025, RN0700, RN0710, MB 229.3/229.1/229.31, Fiat 9.55535-N2 & 9.55535-M2/S2, BMW LL-01/ LL-04, VW 502.00/505.00, Ford WSS-M2C937, WSS-M2C947-A, WSS-M2C945-A, , Chrysler MS 11106, Porsche A40 Meets quality requirements of most gasoline engine manufacturers in the USA, Europe, Japan and Korea

TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	10W-40
Product code	12413AL
Density at 15 ^o C, g/ml, ASTM D4052	0.867
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	6600 @-25 ^o C
Kinematic Viscosity at 40 ^o C, mm ² /s, ASTM D445	95
Kinematic Viscosity at 100 ^o C, mm ² /s, ASTM D445	14.3
Viscosity Index, ASTM D2270	155
Flash Point(COC), °C, ASTM D92	224
Pour Point, °C, ASTM D97	-36
Total Base Number, mg KOH/g, ASTM D2896	10.2

Note: These characteristics are typical of current production. While future production will conform to current specification, variations in these characteristics may occur.

ATL/PDS/AL/004E/01*, 10.01.22, Page 1/1
*supersedes all previous versions

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment.