

BAHRAIN LUBRICANTS ATF DEXRON III

(Automatic Transmission & Power Steering Fluid)

DESCRIPTION

BAHRAIN LUBRICANTS ATF DEXRON III is synthetic lubricant based on carefully selected highly refined base oils with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

APPLICATIONS

BAHRAIN LUBRICANTS ATF DEXRON III is recommended for use in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements (use in GM automatic transmissions pre 2005).

NB: Do NOT use where Dexron VI, Mercon V or Mercon SP or LV are required.

PRODUCT BENEFITS

- Anti-wear protection: significantly extended transmission life.
- Extended oil life: excellent thermal and oxidation stability
- Increased clutch band and clutch pack capacity.
- Efficient operation of power steering units in all conditions.
- Enhanced friction durability for smooth transmission performance
- Improved protection of copper and bronze components
- Effective seal compatibility reduces the risk of leakages

RECOMMENDATIONS / SPECIFICATIONS

ALLISON C4

FORD MERCON

GM 6417-M DEXRON III -G

MAN 339 V1/Z1 MB 236.5, 236.9 VOITH H55.6335xx

ZF TE-ML 03D, 04D, 09, 11B, 14A, 17C VOLVO ST D 1273,40 (97340), 41 (97341)

TYPICAL TECHNICAL PROPERTIES

	DEXRON III
Product code	12716AT
Color, VISUAL	RED
Density at 15°C, g/ml, ASTM D4052	0.855
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	34.55
Kinematic Viscosity at 100°C, mm²/s, ASTM D445	7.1
Viscosity Index, ASTM D2270	175
Flash Point(COC), °C, ASTM D92	196
Pour Point, °C, ASTM D97	-42
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	20,000

Note: These characteristics are typical of current production. While future production will conform to current specification, variations in these characteristics may occur.

ATL/PDS/ATF/007a/01*, 10.01.22, Page 1/1 *supersedes all previous versions